



David Hanman Engineering Services

NL100 series group A neon obstacle lamp

A versatile range of long life, low intensity obstacle lamps which meet the current CAA and ICAO requirements.



Lamps are available to suit most voltages:-

- NL/101 12VDC (10.5-15.0) NL/102 24VDC (18-30)
- NL/103 48VDC (38-60)
- NL/106 115VAC
- NL/107 230VAC
- Neon Spiral Part No 2/NS/101

Complies with the following:-

BS 3224 Part 6 Obstacle Light Fittings

ICAO Annex 14, Vol. 1 - Aerodromes

ICAO Annex 14, Vol. 2 - Heliports

CAP 168 " BSEN 55015 Class B - Emissions

BSEN 55011 Class B - Radiation

Suitable for ambient temperatures from -20°C to +50°C

Protection rating to IP 56 " Suitable for use on hot chimneys

Nominal light output = 12cd " Power Consumption Nominal 6 Watts

Operating parameters: DC see below Mains AC = +/- 6.0%

Nominal tube life = 20000 hours

Corrosion resistant cast alloy body Red Polyester powder coat

Optional flashing facility " Inbuilt telemetry relay - lamp fail indication Voltage free contacts

Dimensions:- 175mm x 170mm x 260mm high

Packing Spec:- Net Wt. = 3.5 KGs Gross Wt. = 4.0Gs Carton = 200mm x 230mm x 585mm

To order, Contact : sales@davidhanman.com
Our web presence : www.davidhanman.com