



**Dual Polarised Antenna
Type: RXP3G-5**

- ❑ **URBAN 3G APPLICATIONS**
- ❑ **COMPACT LOW-PROFILE RADOME**
- ❑ **EASY PAN & TILT ADJUSTMENT**

The '3G Series' of panel antennas have been designed to easily facilitate the installation of Third Generation Cellular infrastructure into new or existing networks.

The compact RXP3G-5 model provides an attractively-styled unit for urban applications.

The mounting brackets enable both Pan + Tilt options.

Two connectors are provided on the base of the unit.



TECHNICAL SPECIFICATION

MODEL RXP3G-5

Frequency	: 1900 - 2170 MHz
Horizontal Beamwidth	: 60°
Vertical Beamwidth	: 13°
Gain	: 14 dBi
VSWR	: 1.4:1 typical
Fixed electrical downtilt	: 4°
Isolation	: 30dB typical
Front-to-back ratio	: 24 dB
Power handling	: 20 Watts per port
Cross polar discrimination	: 20 dB
IP rating	: IP 66 Standard
Bracket	: Tilt (+2° to -10°), Pan (± 20°)
Connectors	: 2 x 7/16" DIN (socket at bottom)
Dimensions (mm)	: 760 x 170 x 35
Weight (inc. bracket)	: 1.4 Kg

